

### Datasheet

Part# HEUX-X00X00-2XF

### Product Features

- Max 576 MTP/MPO or 144 LC fiber ports in 2U
- Compatible with High Density Fiber Cassettes & Panels
- LC, LC/APC, SC, ST, FC and MTP/MPO Configurations
- Hinged Door on the Rear Allows Easy Access to Adapters
- Accessories Included for Fiber Cable Entry & Management



### Description

2U Rack Mount Fiber Enclosure High Density Series fiber cassettes or adapter panels. This Rack Mount Fiber Enclosure is compatible with Qty. 6 of OptoSpan High Density Series LGX Fiber Cassettes or LGX Adapter Panels. Each 2U Rack Mount Fiber Enclosure can accommodate a maximum of 144 fiber ports. It is constructed with 16 Gauge Steel and coated with black electrostatic polyester powder coat paint.

### Technical Specifications

Total Fiber Count	
Modular/Fixed	Modular
Fiber Optic Mode	None
Num. of Modules	6
Front Adapter Type	
Front Port Count	
Front Port Fiber Count	
Insertion Loss (MPO)	-
Insertion Loss (LC/SC)	
Dimensions	17"W x 14"D x 3.5"H

Height	2U
Front (Angled/Flat)	Flat
Polarity	-
#Ports Per Module	-
Rear Adapter Type	
Rear Port Count	
Rear Port Fiber Count	
Return Loss (MPO)	-
Return Loss (LC/SC)	
Construction Material	16 Gauge Steel (Black)