

Datasheet

Part# HEUX-X00X00-4XF

Product Features

- Max 1152 MTP/MPO or 288 LC fiber ports in 4U
- Compatible with High Density Fiber Cassettes & Panels
- LC, LC/APC, SC, ST, FC and MTP/MPO Configurations
- Hinged Door on the Rear Allows Easy Access to Adapters
- Accessories Included for Fiber Cable Entry & Management



Description

4U Rack Mount Fiber Enclosure High Density Series without fiber cassettes or adapter panels. This Rack Mount Fiber Enclosure is compatible with Qty. 12 of OptoSpan High Density Series LGX Fiber Cassettes or LGX Adapter Panels. Each 4U Rack Mount Fiber Enclosure can accommodate a maximum of 288 fiber ports. It is constructed with 16 Gauge Steel and coated with black electrostatic polyester powder coat paint.

Technical Specifications

Total Fiber Count	
Modular/Fixed	Modular
Fiber Optic Mode	None
Num. of Modules	12
Front Adapter Type	
Front Port Count	
Front Port Fiber Count	
Insertion Loss (MPO)	-
Insertion Loss (LC/SC)	
Dimensions	17"W x 14"D x 7"H

Height	4U
Front (Angled/Flat)	Flat
Polarity	-
#Ports Per Module	-
Rear Adapter Type	
Rear Port Count	
Rear Port Fiber Count	
Return Loss (MPO)	-
Return Loss (LC/SC)	
Construction Material	16 Gauge Steel (Black)