

## Datasheet

Part# HPP9-SDZSDZ-1XF

### Product Features

- 24 SC Ports in 1U
- Qty. 2 Fiber Adapter Panel(s) with 12 SC
- Available with up to 288 LC Fiber Ports in 4U
- Splicing Kit Available (Optional)
- LC Pigtailed, splice trays and Splice Sleeves Available



### Description

OptoSpan Part# HPP9-SDZSDZ-1XF is a Matrix-HD Series high density, modular (LGX Fiber Adapter Panel), fully-loaded Single-mode SC Flat 1U fiber patch panel. It is a complete LGX Fiber Adapter Panel based turnkey solution with a total of 24 SC fibers (12 Duplex SC) in 1U. This modular fiber patch panel is factory pre-loaded with Qty. 2 12 fiber SC Duplex LGX Fiber Adapter Panels for quick implementations in 10/100G networks.

The OptoSpan Matrix High Density fiber patch panels are designed to accommodate high density applications in Data Centers and Telecommunication environments. This factory pre-populated and tested Fiber Patch Panel saves on-site installation time and increase reliability. The design of enclosure allows for easy connection to the SC adapters using OptoSpan's multi-fiber optical patch cords (sold separately) and is mountable in a standard 19in or 23in rack or cabinet frame. It is constructed with 16 Gauge Steel and coated with black electrostatic polyester powder coat paint. Please contact us to inquire about compatible OptoSpan patch cords to use with this Fiber Patch Panel. Maximum expandable to 36 SC ports.

### Technical Specifications

Total Fiber Count	24
Modular/Fixed	Modular
Fiber Optic Mode	OS2
Num. of Modules	2
Front Adapter Type	SC
Front Port Count	12
Front Port Fiber Count	Duplex
Insertion Loss (MPO)	-
Insertion Loss (LC/SC)	.18 (Avg) ; .30 (Max)
Dimensions	17"W x 14"D x 1.75"H

Height	1U
Front (Angled/Flat)	Flat
Polarity	-
#Ports Per Module	12
Rear Adapter Type	SC
Rear Port Count	12
Rear Port Fiber Count	Duplex
Return Loss (MPO)	-
Return Loss (LC/SC)	>55/65 dB (UPC/APC)
Construction Material	16 Gauge Steel (Black)