

Datasheet

Part# HPP3-LDCX00-2XF

Product Features

- 144 LC Ports in 2U
- Qty. 6 Fiber Adapter Panel(s) with 24 LC
- Available with up to 288 LC Fiber Ports in 4U
- Splicing Kit Available (Optional)
- LC Pigtailed, splice trays and Splice Sleeves Available



Description

OptoSpan Part# HPP3-LDCX00-2XF is a Matrix-HD Series high density, modular (LGX Fiber Adapter Panel), fully-loaded Multimode (OM3/OM4) LC Flat 2U fiber patch panel. It is a complete LGX Fiber Adapter Panel based turnkey solution with a total of 144 LC fibers (72 Duplex LC) in 2U. This modular fiber patch panel is factory pre-loaded with Qty. 6 24 fiber LC Duplex LGX Fiber Adapter Panels for quick implementations in 10/100G networks. The OptoSpan Matrix High Density fiber patch panels are designed to accommodate high density applications in Data Centers and Telecommunication environments. This factory pre-populated and tested Fiber Patch Panel saves on-site installation time and increase reliability. The design of enclosure allows for easy connection to the LC adapters using OptoSpan's multi-fiber optical patch cords (sold separately) and is mountable in a standard 19in or 23in rack or cabinet frame. It is constructed with 16 Gauge Steel and coated with black electrostatic polyester powder coat paint. Please contact us to inquire about compatible OptoSpan patch cords to use with this Fiber Patch Panel. Maximum expandable to 144 LC ports.

Technical Specifications

Total Fiber Count	144
Modular/Fixed	Modular
Fiber Optic Mode	OM3/OM4
Num. of Modules	6
Front Adapter Type	LC
Front Port Count	72
Front Port Fiber Count	Duplex
Insertion Loss (MPO)	-
Insertion Loss (LC/SC)	.15 (Avg) ; .30 (Max)
Dimensions	17"W x 14"D x 3.5"H

Height	2U
Front (Angled/Flat)	Flat
Polarity	-
#Ports Per Module	24
Rear Adapter Type	
Rear Port Count	
Rear Port Fiber Count	
Return Loss (MPO)	-
Return Loss (LC/SC)	-
Construction Material	16 Gauge Steel (Black)