

Datasheet

Part# UPL9-LQWVZT-1AF

Product Features

- 96 LC Fiber Ports in 1RU with Flat Front
- 8 MTP Elite (12 Fiber) Connectors in Rear for Core Connection
- Available with 12 Fiber MTP (10/40G) OR 24 Fiber MTP
- Compact Design with Panel depth of less than 11"
- Premium Front & Rear Wire Management Trays Included



Description

OptoSpan Part# UPL9-LQWVZT-1AF is a fully-loaded Matrix-UD Series ultra-high density Single-mode LC rack-mount MTP patch panel that offers 96 LC ports (24 Quad LC) in 1RU. In the rear, it offers 8 Low Loss MTP Elite (12 Fiber Connector) for connection to MPO/MTP backbone trunk. Pre-configured for Polarity Method A (Pin1 - Pin1) & type A (key-up to key-down) MTP/MPO adapters. Internally, it contains low loss Low Loss MTP Elite-LC assemblies to deliver lower insertion losses for high speed networks that demand low power budgets. This Single-mode MTP patch panel configuration is ideally suitable for 40G/100G networks.

The OptoSpan Matrix Ultra Density MTP patch panel are designed to accommodate high density applications in Data Centers and Telecommunication environments. This factory pre-populated and tested MTP patch panel saves on-site installation time and increase reliability. The Ultra Density Series panels are designed to facilitate better cable management and provide more room for interaction with the LC adapters. The design of enclosure allows for easy connection to the LC & Low Loss MTP Elite connectors using OptoSpan’s multi-fiber optical patch cords (sold separately) and is mountable in a standard 19in or 23in rack or cabinet frame. It is constructed with 16 Gauge Steel and coated with black electrostatic polyester powder coat paint. Please contact us to inquire about compatible OptoSpan patch cords with proper polarity and terminations to use with this MTP patch panel.

Technical Specifications

Total Fiber Count	96
Modular/Fixed	Fixed
Fiber Optic Mode	OS2
Num. of Modules	-
Front Adapter Type	LC
Front Port Count	24
Front Port Fiber Count	Quad
Insertion Loss (MPO)	.10dB (Avg); .35dB (Max)
Insertion Loss (LC/SC)	.18 (Avg) ; .30 (Max)
Dimensions	17.5'W x 8.7'D x 1.75'H

Height	1U
Front (Angled/Flat)	Flat
Polarity	Method A
#Ports Per Module	-
Rear Adapter Type	MTP Elite
Rear Port Count	8
Rear Port Fiber Count	12
Return Loss (MPO)	> 60dB
Return Loss (LC/SC)	>55/65 dB (UPC/APC)
Construction Material	16 Gauge Steel (Black)