

Cisco XFP-10GLR-OC192SR Datasheet

For Informational Purposes Only

Data Compiled by SanSpot

Cisco XFP-10GLR-OC192SR Duplex XFP 10Gbps 2 km SMF DDM 1310nm

XFP-10GLR-OC192SR Features

- Cisco 10GBASE-LR/LW Ethernet XFP
- Up-to 2 km over SMF @ 10Gbps
- 1310nm Duplex XFP Transceiver
- 0°C - 70°C Operating Case Temperature
- SFF-8724 Digital optical monitoring
- Hot-swappable for XFP LC ports
- Cisco 90 day standard warranty
- Cisco XFP can be covered by SMARTnet
- XFP MSA & IEEE 802.3ae
- Cisco XFP-10GLR-OC192SR is RoHS compliant



Applications

- 10GBASE Ethernet
- OC-192/STM-64

Description

The Cisco XFP-10GLR-OC192SR 10GBASE-LR/LW Ethernet transceiver is a Duplex XFP transceiver for optical communications, rated for distances up to 2 km and a maximum bandwidth of 10Gbps. The XFP-10GLR-OC192SR transceiver operates at 1310nm wavelength. Cisco Multirate 10GBASE-LR and OC-192/STM-64 SR-1 XFP Module for SMF.

The Cisco XFP Module offers customers a variety of 10 Gigabit Ethernet and Packet-over-SONET/SDH (POS) connectivity options for data center, enterprise wiring closet, and service provider transport applications.

Note: Due to manufacturer restrictions, Cisco XFP-10GLR-OC192SR is a non-cancellable &

About this Data Sheet

This data sheet has been compiled by SanSpot as a service to its clients and is based on publicly available information from the manufacturer at the time of this publication. For most up-to-date information, please visit manufacturer website. SanSpot is not responsible for omissions or typographical errors.